

Mini Flood Light

70W | Colour Tunable | 120-347V



Ideal for landscaping, patio, and security lighting, signs and building facades Excellent replacement for quartz halogen fixtures

Die-Cast Aluminum Housing
with cooling fins for superior heat dissipation



High-Impact Polycarbonate Lens/Optics

Complete With Yoke Mount
Knuckle mount sold separately

Wattage Adjustable
(70-100%)

Built-in Photocell

56 LED Chips
for even illumination

0.5m Power Cord

Colour Tunable
3000K / 4000K / 5000K

Rugged Polyester Powder Coat Finish
(Bronze)



Optional Accessories:
Knuckle Mount (FLM-KNL)
Slip Fit (FLM-SF)

Suggested Substitutions:
FLM-50W-3CCT-LV
FLM-90W-3CCT-UD

TECHNICAL DATA



LIGHT SPECIFICATIONS


Lumens	9,526 lm
Efficacy	129 lm/W @ 3000K
CCT	3000K / 4000K / 5000K
CRI	80
Dimmable	Yes
L70 Life	50,000 hrs
Warranty	10-year

APPROVALS AND LISTINGS


cUL	E482965
DLC	PL2VU305QAQX

DIMENSIONS


Yoke Mount (Standard)



Knuckle Mount (Sold Separately)



Slip Fit (Sold Separately)



ELECTRICAL

Wattage	70W (Adjustable 70-100%)
Voltage	120-347V
Power Factor	0.9
THD	15%
Operating Temp	-40 to 50°C


CONSTRUCTION

Housing	Die-Cast Aluminum
Finish	Bronze
IP Rating	IP65
Carton Weight	15.4 kg
Carton Qty	5
Carton Dimensions	394 x 338 x 362 mm

ACCESSORIES (SOLD SEPARATELY)

Knuckle Mount	FLM-KNL
Slip Fit	FLM-SF

ISOCANDELA



ILLUMINANCE AT A DISTANCE

